





SPECIFICATIONS	PF-5042-02-02
Flow Rate	190 GPM
Filtration Area	9.60 sq ft
Valve Size	3"
System Inlet Connection	3" Flg
System Outlet Connection	2 1/2" Flg
Waste Connection	2 1/2" Flg
Backwash Connection	2 1/2" Flg
Pump Motor	5 HP
Est. Weight, Dry	2420 lbs
Est. Weight, Operating	3130 lbs

^{*}Shipping weight includes media

PF-5042-02-02 SPECIFICATION SHEET CLOSED LOOP PUMP PACKAGE SYSTEM

Features:

- Removes particulate as low as 5 microns
- 150 psi working pressure
- Fully assembled skid package
- One year limited warranty

Options:

- Higher pressure ratings
- ASME code stamped vessel

SYSTEM COMPONENTS

Filter Vessel:

- Non-code carbon steel vessel
- · Fusion bonded, polyester coated
- Pressure gauges & manual air vent valve
- Cast iron butterfly valves

Electrical Controls:

- UL labeled control panel with NEMA 4X Enclosure
- Adjustable solid state timer
- Short circuit and Motor overload protection
- Electric actuators

Pump:

- Close coupled, end suction centrifugal pump
- TEFC motor

Backwash Controls:

- 24 Hour time clock
- Manual push button

Skid:

 Fusion-bond polyester coated carbon steel

Interconnecting Pipe:

• Sch.40 Carbon steel piping



