



SPECIFICATIONS	PF-65-080		
Flow Range	1170-2355 GPM		
System Inlet Connection	8" Flg		
System Outlet Connection	8" Flg		
Purge Connection	1 1/2" fpt		
Manual Air Bleed Valve	1/4" fpt		
Volume	52 GAL		
Est. Weight, Dry	625 lbs		
Est. Weight, Operating	1056 lbs		
Handhole – Inspection/Cleanout	4" x 6"		

ENGINEERING • MANUFACTURING • SERVICE

PF-65-080 SPECIFICATION SHEET FLANGED SEPARATOR

Features:

- True tangential entry
- 150 psi working pressure
- Five year limited warranty
- Electrically actuated ball valve
- 22 1/2° Profile vessel

Options:

- Automatic purge
- Isolation valve kit
- Wall mounting brackets/legs
- Inspection port

SYSTEM COMPONENTS

Separator :

- Carbon steel construction
- Fusion-bond polyester coated vessel
- Manual air bleed valve
- Inlet/Outlet pressure gauges

Electrical Controls :

- NEMA 4X Enclosure
- Short circuit protection
- Purge switch selector
- Adjustable purge timer

PRESSURE DROP vs. FLOW RATE								
Pressure Drop	3 psi	4 psi	6 psi	8 psi	10 psi	12 psi	CV Factor	
Flow (GPM)	1177	1359	1664	1922	2148	2354	679.4	

*(Flow rate / CV values may vary slightly

To determine the approximate pressure drop at flow rates not shown in this chart, use the following formula Δ P= (FLOW RATE / CV)²

CV Factor: CV is defined as the flow in gallons per minute (GPM) that will produce a one pound pressure drop across the separator

