



PUROFLUX Corporation

EZ Selection Guide for Marley Sweeper Piping

2121 Union Place
 Simi Valley, CA 93065
 Phone: (805) 579-0216
 Fax: (805) 579-6005
 Email: sales@puroflux.com
 Website: www.puroflux.com

1. The filtration / separation selections are based on current available Marley data for single cell cooling tower models with factory installed sweeper piping. (Actual flows may vary, check with your local dealer.)
2. This guide was designed to aid in the selection of standard catalog Puroflux equipment for Marley factory installed sweeper piping.
3. The PF-63 models include a recovery vessel as standard.
4. The PF-64 models include an automatic purge valve as standard.
5. Media filter models listed utilize tower water for the backwash source. To specify city water as the backwash source, change the last two digits to "02". (Ex: PF-3042-02-02)
6. Please contact Puroflux or your local representative for multiple cell and/or slip stream applications not shown.

Marley NC Series			
Model Number	Sweeper Piping Flow Rate (GPM)	Suggested Media Filter	Suggested Separator
8401	147.2	PF-3036-02-01	PF-63-025 (or) PF-64-025
8402			
8403			
8405	206	PF-3042-02-01	PF-63-030 (or) PF-64-030
8407	282.8	PF4054-02-01	PF-63-040A (or) PF-64-040A
8409			
8411			
8412			
8413			
8414			

Marley MD Series			
Model Number	Sweeper Piping Flow Rate (GPM)	Suggested Media Filter	Suggested Separator
5008	104.6	PF-3030-02-01	PF-63-020 (or) PF-64-020
5010	121.4	PF-3036-02-01	PF-63-020 (or) PF-64-020
5016	161.4	PF-3042-02-01	PF-63-025 (or) PF-64-025
5018	152.4	PF-3036-02-01	PF-63-025 (or) PF-64-025